

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
21 June 2001 (21.06.2001)

PCT

(10) International Publication Number  
**WO 01/43817 A1**

(51) International Patent Classification<sup>7</sup>: **A61N 1/32**

**JAROSZESKI, Mark, J.**; 14621 Grenadine Drive #4,  
Tampa, FL 33613 (US).

(21) International Application Number: **PCT/US99/29911**

(74) **Agent: HARTT, Jacqueline, E.**; Allen, Dyer, Doppelt,  
Milbrath & Gilchrist, P.A., Suite 1401, 255 South Orange  
Avenue, P.O. Box 3791, Orlando, FL 32802-3791 (US).

(22) International Filing Date:  
15 December 1999 (15.12.1999)

(25) Filing Language: English

(81) **Designated States (national)**: AE, AL, AM, AT, AU, AZ,  
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,  
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,  
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,  
LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO,  
RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG,  
UZ, VN, YU, ZA, ZW.

(26) Publication Language: English


(71) **Applicant: UNIVERSITY OF SOUTH FLORIDA**  
[US/US]; Division of Patents and Licensing, FAO 126,  
4202 East Fowler Avenue, Tampa, FL 33620 (US).

(84) **Designated States (regional)**: ARIPO patent (GH, GM,  
KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent  
(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent  
(AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU,

(72) **Inventors: HELLER, Richard**; 509 Terrace Hill Drive,  
Temple Terrace, FL 33617 (US). **GILBERT, Richard**;  
10740 N. 56th Street #108, Tampa, FL 33617 (US).

[Continued on next page]

(54) Title: **ELECTROPORATION DEVICE AND METHOD**



(57) **Abstract:** A device (10) for manipulating a molecule (M) *in vivo* relative to a target tissue (T) in three dimensions includes a support (11) and at least one member affixed to and extending away from the support. The member has at least two discrete and separately activatable electrodes (13, 14, 15). The electrodes are configured to establish a first electromagnetic field between selected electrodes sufficient to manipulate a molecule relative to a target tissue. The electrodes are further configured to establish a second, typically higher-level, electromagnetic field sufficient to cause transient permeability of a cell membrane within the target tissue. A third electromagnetic field may also be applied to cause further translation of the molecule into an electroporeabilized cell and/or manipulated with respect to the tissue. Thus three-dimensional manipulation of the molecule relative to the target tissue is effected to optimize a desired positioning thereof, such as entry into a cell.

WO 01/43817 A1



MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *With international search report.*

## ELECTROPORATION DEVICE AND METHOD

### BACKGROUND OF THE INVENTION

#### **Cross-Reference to Related Application**

This application claims priority from previously filed provisional application, "Methods and Apparatus for Three Dimensional Distribution of Molecules within Tissues and Cells *in Vivo*," Serial No. 60/069,876, filed December 17, 1997.

#### **Field of the Invention**

The present invention relates to methods and apparatus for delivering molecules into a target cell, and, more particularly, to such methods and apparatus for achieving such delivery through electroporation and electromigration.

#### **Description of Related Art**

The effect of electromagnetic fields on cell membranes has been studied since the 1960s. Early research focused on describing observations that an applied electric field can reversibly break down cell membranes *in vitro*. Throughout the 1970s the topic was more common in the literature and continued to focus on describing the phenomenon that resulted from brief exposure to intense electric fields as well as the entry of exogenous molecules to the cell interior as a result of membrane breakdown. Applications began to emerge along with a better understanding of reversible membrane breakdown in the 1980s.

Prior research led to the current understanding that exposure of cells to intense electric fields for brief periods of time temporarily destabilized membranes. This effect has been described as a dielectric breakdown due to an induced transmembrane potential, and was termed "electroporation," or "electropermeabilization," because it was observed that molecules that do not normally pass through the membrane gain intracellular access after the cells were treated with electric fields. The porated state was noted to be temporary. Typically, cells remain in a destabilized state on the order of minutes after electrical treatment ceases.

The physical nature of electroporation makes it universally applicable. A variety of procedures utilize this type of treatment, which gives temporary access to the cytosol. These include production on monoclonal antibodies, cell-cell fusion, cell-tissue fusion, insertion of membrane proteins, and genetic transformation. In addition, dyes and fluorescent molecules have been used to investigate the phenomenon of electroporation. A notable example of

loading molecules into cells *in vivo* is electrochemotherapy. The procedure utilizes a drug combined with electric pulses as a means for loading tumor cells with an anticancer drug, and has been performed in a number of animal models and in clinical trials by the present inventors. Also, plasmid DNA has been loaded into rat liver cells *in vivo* (Heller et al., *FEBS Lett.* **389**, 225-28).

Protocols for the use of electroporation to load cells *in vitro* typically use a suspension of single cells or cells that are attached in a planar manner to a growth surface. *In vivo* electroporation is more complex because tissues are involved. Tissues are composed of individual cells that collectively make up a three-dimensional structure. In either case, the effects on the cell are the same. FIGURE 1 illustrates details of the electrical treatment procedure. Electrodes and electrode arrays for delivering electrical waveforms for therapeutic benefit, including inducing electroporation, have been described by Bernard (WO 98/47562).

The loading of molecules by electroporation *in vitro* as well as *in vivo* is typically carried out by first exposing the cells or tissue of interest to a drug or other molecule (FIG. 2). The cells or tissue are then exposed to electric fields by administering one or more direct current pulses. Electrical treatment is conducted in a manner that results in a temporary membrane destabilization with minimal cytotoxicity. The intensity of electrical treatment is typically described by the magnitude of the applied electric field. This field is defined as the voltage applied to the electrodes divided by the distance between the electrodes. Electric field strengths ranging from 1000 to 5000 V/cm have been used for delivering molecules *in vivo* and are also specific to the cells or tissue under investigation. Pulses are usually rectangular in shape; however, exponentially decaying pulses have also been used. The duration of each pulse is called *pulse width*. Molecule loading has been performed with pulse widths ranging from microseconds ( $\mu$ s) to milliseconds (ms). The number of pulses delivered has ranged from one to eight. Typically, multiple pulses are utilized during electrical treatment.

For molecules to be delivered to the cell interior by electroporation, it is important that the molecule of interest be near the exterior of the cell membrane when in the cell is in a permeabilized state. It is also important to have molecules near substantially all cells within a treated tissue volume in order to provide efficient delivery to substantially all cells within the treatment volume.

Currently, molecules are injected systemically, via methods well known to those of skill in the art, or directly into the treatment site.- No attempt is made to produce a specific distribution. These methods do not ensure that the distribution of molecules is sufficient to provide effective delivery to substantially all the cells.

Electropermeabilization of tumor cell membranes *in vivo* has been reported (Rols et al., *Nature Biotechnology* **16**, 173, 1998) using applied electric pulses from surface electrodes in contact with the skin. A protein can be transferred into or and expressed by the cells by incorporating either the protein or a plasmid carrying a reporter gene. The efficiencies of transfer for the protein and plasmid were, respectively, 20 and 4%.

A first type of electrode known in the art comprises parallel-plate electrodes placed on opposite sides of the tumor. Other electrodes known in the art at the present time comprise needles that are inserted into or around the tissue of interest. Electric fields are applied in only two dimensions of the three-dimensional tissue matrix. This limits the area of each cell that can be electroporated (FIG. 1), which reduces delivery efficiency.

A two-dimensional array of needles has also been disclosed (Gilbert et al., *Biochim. Biophys. Acta* **1334**, 9, 1997; U.S. Pat. No. 5,702,359) in which circularly disposed pairs of needles surround a target tissue. Pulses of opposite polarity are applied across each pair of needles in a predetermined sequence, which has been shown to improve tumor regression in a mouse melanoma study.

Electrodes and methods known in the art do not provide molecule movement during the preelectroporation period to enhance molecular distribution nor in the postelectroporation time period, when the cells are in a state of increased membrane permeability. The movement of molecules within the tissue is believed to effect an increase in the delivered quantity of molecules by enhancing movement into the cells.

### **SUMMARY OF THE INVENTION**

It is therefore an object of the present invention to provide an improved device and method for manipulating molecules adjacent and/or within a target tissue site.

It is an additional object to provide such a device and method for manipulating molecules in three-dimensional space such as a tissue volume element.

It is a further object to provide such a device and method that can provide a desired electromagnetic field distribution adjacent and/or within a target tissue.

It is another object to provide such a device and method that can be configured to activate a multicomponent labile system at a desired site.

5 It is yet an additional object to provide a system for effecting tumor reduction.

It is yet a further object to provide a system for effecting *in vivo* gene transfer to cells via electroporation.

10 These objects and others are attained by the present invention, a device for manipulating a molecule *in vivo* relative to a target tissue in three dimensions. The device comprises a support and at least one member affixed to and extending away from the support. The member has at least two discrete electrodes, each electrode in independent circuit communication with a respective portion of a source of electrical energy and therefore being differentially activatable.

15 The discrete electrodes are configured to establish a first electromagnetic field *in vivo* between selected electrodes sufficient to manipulate a molecule translationally relative to a target tissue. The electrodes are further configured to establish a second electromagnetic field sufficient to cause transient permeability of a cell membrane within the target tissue. In a particular embodiment the electrodes are also configured to establish a third electromagnetic field sufficient to manipulate a molecule translationally following the second field to continue enhancing molecular distribution and/or uptake at cells. Typically the first and the third field levels will be lower than that of the second, although this is not intended as a limitation.

20 In an alternate embodiment, a system includes at least two members extending from a support. A first member includes at least one electrode as described above; a second member includes at least two electrodes. Such an arrangement permits triangulation between the independently activatable electrodes.

25 In a particular embodiment the electrodes are activatable in a predetermined sequence, which may include sequential or simultaneous activation of any or all of the electrodes.

30 The device can be used, for example, with alternating current, direct current, pulsed alternating current, pulsed direct current, high- and low-voltage alternating current with variable frequency and amplitude, variable direct current waveforms, variable alternating

current signals biased with variable direct current waveforms, and variable alternating current signals biased with constant direct current.

Several embodiments of the methods of the present invention include the use of a device as described above to enhance the delivery of a molecule such as a bioactive molecule, nucleic acid, amino acid, polypeptide, protein, antibody, glycoprotein, enzyme, oligonucleotide, plasmid DNA, chromosome, or drug, although this list is not intended to be exhaustive or limiting. In a related embodiment the device may be used to cause the electromigration of at least two components of a multicomponent reactive system into apposition to permit a reaction to occur at a desired target tissue site. The target tissue may comprise a tumor, and organ, or wound site.

The features that characterize the invention, both as to organization and method of operation, together with further objects and advantages thereof, will be better understood from the following description used in conjunction with the accompanying drawing. It is to be expressly understood that the drawing is for the purpose of illustration and description and is not intended as a definition of the limits of the invention. These and other objects attained, and advantages offered, by the present invention will become more fully apparent as the description that now follows is read in conjunction with the accompanying drawing.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

**FIG. 1** (prior art) Conceptual two-dimensional depiction of electroporation of a cell subjected to an electromagnetic field. Regions of membrane breakdown, depicted as pores, are formed at the ends of cells facing the electrodes. Electromagnetic field exposure is achieved by applying a potential between electrodes - and +.

**FIG. 2** (prior art) The process of delivering molecules by electroporation. **FIG. 2A.** Cells *in vitro* or *in vivo* are exposed to the molecule of interest. **FIG. 2B.** Direct current pulses are administered to the cells to cause a temporary membrane destabilization that allows the molecules to more freely enter the cell interior. **FIG. 2C.** Cells return to their normal state after pulsation, leaving the molecule within the cells.

**FIG. 3 A** first embodiment of one electrode-bearing member of a molecule manipulator, including radially disposed coaxial electrodes spaced apart by nonconductive material.

**FIG. 4** A molecule manipulator including a support and plural members as in FIG. 3.

**FIG. 5** A second embodiment of one electrode-bearing member of a molecule manipulator, including circumferential bands of electrodes disposed along a generally cylindrical electrode.

**FIG. 6** A molecule manipulator including a support and plural members as in FIG. 5.

**FIG. 7** The use of a molecule manipulator to bring components of a multicomponent reactive system into apposition at a target tissue site.

### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

A description of the preferred embodiments of the present invention will now be presented with reference to FIGS. 3-7.

A first embodiment of a device **10** for manipulating a molecule **M** *in vivo* relative to a target tissue **T** (FIGS. 3 and 4) comprises a support **11** that is adapted to reside outside the site of the target tissue **T**, here shown as atop the skin **S**, although this is not intended as a limitation. At least one member **12**, here shown as four members **12**, are affixed to and extend away from the support **11**. The members **12** are preferably disposed about the support **11** in spaced relation from each other and are configured to surround a periphery of and/or penetrate into at least a portion of the target tissue **T**, with at least a lower portion of the members **12** penetrating the skin **S** (or other organ or tissue) to reach the target tissue **T**. Here the target tissue is **T** represented as a tumor, although this is not intended to be a limitation.

Each member **12** has at least two discrete electrodes disposed in axially spaced-apart relation from each other, here shown as three electrode portions **13,14,15**. Each electrode **13-15** is in circuit communication with a respective portion of a source **50** of electrical energy. The term "in circuit communication" as used herein is used to describe (1) devices that are directly or indirectly electrically connected with each other; (2) devices having other devices or combinations of devices (e.g., breakers, relays, buffers, drivers, transmitters, receivers, and decoders) between them; (3) devices in optical communication with each other (via, e.g., an optoisolator or fiber optic link); (4) devices in electromagnetic communication with each other (via, e.g., radio frequency transmitter and receiver pair); (5) devices connected by and through



other structures allowing them to communicate with each other; and (6) any combination of any of the above.

In a preferred embodiment this source comprises a pulse generator such as is known in the art (e.g., a PA-2000 or PA-4000, both from Cyto Pulse Sciences, Inc., Columbia, MD; a T820, BTX, Inc., San Diego, CA) and adapted to deliver pulses of a predetermined shape, voltage, duration, and separation. In particular, the source **50** should be adapted to deliver voltage to each electrode **13-15** for establishing a lower-level and a higher-level electromagnetic field *in vivo* between selected electrodes. Selective control of the application of electrical signals between the individual electrodes can be accomplished in different ways, e.g., via the PA-201 Programmable Pulse Switch in combination with the PA-4000 generator (both from Cyto Pulse Sciences, Inc., Columbia, MD) or it can be done manually, mechanically, or electrically.

The lower-level field is for manipulating (e.g., causing the electromigration of) the molecule **M** in three-dimensional fashion relative to the target tissue **T**, here shown as a mass. The higher-level field is for causing transient permeability of a cell membrane within the target tissue **T**. Such a permeability is useful for permitting the molecule **M** to enter the interior of the cell (see FIGS. 1 and 2). A lower-level field can also be applied following the application of a higher-level field to enhance molecule distribution within the target tissue and/or cause movement of the molecule(s) into the cell interior of the permeabilized cell by electroporation.

In the first embodiment, the member **12** comprises an elongated and pointed core electrode **13** that is made of a conductive material. A nonconductive insulator sleeve **16** is positioned in surrounding relation to a portion of the core electrode **13**, with a bottom portion of the core electrode **13** protruding and thus exposed.

A first outer electrode **14** is positioned in surrounding relation to a portion of the sleeve **16**, with a bottom portion of the sleeve **16** protruding therefrom and thus exposed.

A second sleeve **17** is positioned in surrounding relation to a portion of the first outer electrode **14**, with a bottom portion of the second electrode **14** protruding therefrom and thus exposed.

A second outer electrode **15** is positioned in surrounding relation to a portion of the second sleeve **17**, with a bottom portion of the second sleeve **17** protruding therefrom and thus exposed.

A third sleeve **18** is positioned in surrounding relation to a portion of the second outer electrode **15**, with a bottom portion of the second outer electrode **15** protruding therefrom and thus exposed.

In a prototype embodiment, which is not intended as a limitation, the device **10** comprises a stainless steel 30-gauge needle as the core electrode **13** placed in the hollow space of a 25-gauge hypodermic tubing as the first outer electrode **14** with a layer of nonconductive insulation between the electrodes **13,14** as the first sleeve **16**. A layer of insulation is placed over the first outer electrode **14** to serve as second sleeve **17**, and a section of 23-gauge tubing, serving as second outer electrode **15**, is placed over the second sleeve **17**. Insulation placed over the second outer electrode **15** serves as third sleeve **18**. The bottom portions of each of these elements are exposed to form a series of conductive bands **13-15** separated by nonconductive regions **16-18**.

This arrangement provides three electrodes exposed to the exterior with an insulator between each adjacent pair of electrodes. It can be appreciated by one of skill in the art that any number of electrodes and insulators could be successively configured in overlapping fashion to produce a multielectrode member tailored to a particular application based upon such considerations as, for example, the size of the target tissue and the space available.

Each electrode **13-15** has an independent lead **19, 19', 19''**, respectively, affixed to its top end to provide the circuit communication with the pulse generator.

In use the members **12** are typically arranged in opposing spaced-apart pairs, so that at least one electrode on each of a pair of members **12** can be adapted to provide at least one pair of opposite-polarity voltages approximately simultaneously. Further, it may be desired to selectively apply electrical potentials to each electrode pair in a predetermined pattern. Such a means for imposing a preselected pattern may include, for example, a software program for driving a pulse generator to deliver signals to each selected electrode in the preselected pattern.

It can be seen that three-dimensional manipulation can be effected by activating opposing pairs of electrodes at different axial levels to induce molecular movement and/or electropermeabilization along a desired pathway. For example, activating the pair **13-13'** would induce movement generally in a plane normal to the member **12**, whereas activating the pair **13-15'** would induce movement at an angle relative to the plane. These presupposed movements are, of course, subject to other conditions within and surrounding the tissue, and are only to be construed as relative and indicative of possible general directionalities achievable by the devices of the present invention.

A second embodiment of a device **20** for manipulating a molecule **M** *in vivo* relative to a target tissue **T** (FIGS. 5 and 6) comprises a support **21** and at least one member **22**, here shown as four members **22**, affixed to and extending away from the support **21**. The members **22** are preferably disposed about the support **21** in spaced relation from each other and are configured to surround a periphery of and/or penetrate into at least a portion of the target tissue **T**. In FIG. 6 the target tissue is **T** represented as a tumor, although this is not intended to be a limitation.

Each member **22** has at least two discrete electrodes, here shown as five electrodes **23-27** configured as circumferential rings disposed about a generally cylindrical nonconducting core post **28**. As above, each electrode **23-27** is in independent circuit communication with a respective portion of a source **50** of electrical energy. Such independent circuit communication may be formed, for example, by respective insulated leads **29** extending through the core **28** from the top end to each ring electrode **23-27**.

Additionally, the core **28** may have a lumen **30** therein extending from a top opening **33** for dispensing a molecule **M** to a tissue through a portal **31**. The portal **31** in one embodiment may be adjacent an electrode or may **31'** be at the core's tip **32**, which in a particular embodiment may be pointed.

Several embodiments of methods of the present invention will now be disclosed. These methods will be illustrated with the device **10** described above, although this is not intended as a limitation, since either device **10** or **20** could be used therein, or other equivalents appreciated by one of skill in the art.

A first embodiment comprises a method for achieving an improved distribution and delivery of a desired molecule **M** into a target tissue **T**. This method comprises the steps of inserting at least one elongated member **12** into a body tissue generally adjacent and/or within a target tissue **T**. Such an insertion may be aided by any of the visualization techniques known in the art, such as computed tomography, ultrasound, x-radiography, although these are not intended as limitations. A substance that includes the desired molecule **M**, such as a solution thereof, is introduced into the body into an area near the target tissue **T**, either before or after the insertion of the device **10**. A particular introduction method comprises delivering the substance through a lumen **30** and portal **31** as in the embodiment of FIGS. 5 and 6. Any other method of introduction such as known to one of skill in the art may also be employed.

A first electrical potential is established between a pair of electrodes **13-15'** that is sufficient to cause a redistribution and electromigration of the desired molecule **M** toward the target tissue **T**. Then subsequently a second electrical potential is established between a pair of electrodes, which may or may not be the same electrode pair as previously activated. The second potential has a sufficiently high electrical potential to cause electroporation in the target tissue **T** to enhancing a movement of the desired molecule **M** into a cell. An additional, third, low-level field after electroporation induction can be applied to further enhance molecular movement into cells and/or redistribution. Exemplary pulse magnitude and duration ranges include, but are not intended to be limited to, 1-10,000 volts/cm for a duration in the nanosecond to second range. A particular embodiment comprises a pulse or plurality of pulses in a range of 1-500 V/cm for a duration in the millisecond range for the first and the third potentials and a pulse or plurality of pulses in a range of 750-1500 V/cm in the microsecond range for the second potential. Naturally these values are not intended to be limiting, and one of skill in the art will appreciate that, for example, shorter pulses of higher magnitude or longer pulses of lower magnitude may be employed as required to achieve the desired effect.

A second method is for delivering a bioactive molecule to a subcutaneous target tissue **T**. This method comprises the steps of, as above, introducing a substance containing the bioactive molecule **M** systemically or into a subcutaneous area adjacent the target tissue **T**. A device such as device **10** is inserted into a body tissue generally adjacent a target tissue **T**,

and electrode pairs are again activated at a low and high and again low level to achieve, respectively, an electromigration of the bioactive molecule **M** adjacent and within the target tissue **T**, an electroporation of a cell membrane within the target tissue **T** sufficient to permit entry of the bioactive molecule **M** into the cell interior, and additional electromigration within  
5 the target tissue.

A third method (FIG. 7) is for bringing two molecules **M, M'** into apposition at a desired target tissue site **T** for permitting a reaction therebetween, as in multicomponent reactive system, or a cell "bomb." This method comprises the steps of introducing a substance containing a first molecule **M** into a first area **A** adjacent and/or within the target tissue site  
10 **T** and introducing a substance containing a second molecule **M'** into a second area **A'** adjacent and/or within the target tissue site **T**.

Next an electromigration of the first **M** and the second molecule **M'** is caused to a third area **A''** that is adjacent and/or within the target tissue site **T**. The third area **A''** may actually comprise the first **A** or the second area **A'**, or another area distinct therefrom.

15 Next the first **M** and the second **M'** molecule are permitted to react at the third area **A''**.

It may be appreciated by one skilled in the art that additional embodiments may be contemplated, including different electrode configurations adapted to provide high- and low-level fields for causing electromigration and electroporation. In this application, a device  
20 being "configured" to produce an electromagnetic field in vivo means that (i) the portion of the device that comes in contact with body tissue or fluid is made of biocompatible materials, (ii) the electrodes are capable of carrying the current required for electroporation and/or electromigration of living cells in vivo in an electrolyte which may include the tissue being treated, interstitial fluid, injected material at the treatment site, material applied to the target  
25 tissue, and combinations of the foregoing, and (iii) the material between the electrodes on each support member, which may be the same material as the support member, should have a sufficient dielectric constant so that it does not break down as a result of nearby electrodes being of opposite polarity during electrical treatment. Moreover, it will be apparent to those skilled in the art that where an electrode or system is configured to perform both

electromigration and electroporation, such an electrode or system may be used to perform either or both functions.

In the foregoing description, certain terms have been used for brevity, clarity, and understanding, but no unnecessary limitations are to be implied therefrom beyond the requirements of the prior art, because such words are used for description purposes herein and are intended to be broadly construed. Moreover, the embodiments of the apparatus illustrated and described herein are by way of example, and the scope of the invention is not limited to the exact details of construction.

Having now described the invention, the construction, the operation and use of preferred embodiment thereof, and the advantageous new and useful results obtained thereby, the new and useful constructions, and reasonable mechanical equivalents thereof obvious to those skilled in the art, are set forth in the appended claims.

**What is claimed is:**

1. A device for manipulating a molecule *in vivo* relative to a target tissue comprising:

5 a support and at least one member affixed to and extending away from the support, the member having at least two discrete electrodes, each electrode being in circuit communication with a respective portion of a source of electrical energy;

10 the discrete electrodes being configured to establish a first electromagnetic field *in vivo* between selected electrodes sufficient to cause an electromigration of a molecule relative to a target tissue and a second electromagnetic field sufficient to cause transient permeability of a cell membrane within the target tissue.

15 2. The device recited in Claim 1, wherein the second field is higher than the first field.

3. The device recited in Claim 1, wherein the electrodes are disposed in axially spaced-apart relation along the member, and wherein the member further has an insulating material axially interposed between the electrodes.

20 4. The device recited in Claim 1, wherein the member comprises:  
an elongated core electrode comprising a conductive material;  
a nonconductive insulator sleeve positioned in surrounding relation to a portion of the core electrode; and  
25 an outer electrode positioned in surrounding relation to a portion of the sleeve, a bottom portion of the sleeve protruding therefrom.

5. The device recited in Claim 4, wherein the sleeve has a bottom portion adapted to protrude beneath a bottom of the outer electrode.

6. The device recited in Claim 4, wherein the outer electrode comprises a first outer electrode and the sleeve comprises a first sleeve, and further comprising:

a second insulator sleeve positioned in surrounding relation to a portion of the first outer electrode, a bottom portion of the first outer electrode protruding therefrom; and

5 a second outer electrode positioned in surrounding relation to a portion of the second sleeve.

7. The device recited in Claim 6, wherein the first sleeve has a bottom portion positioned to protrude beneath a bottom of the first outer electrode and the second sleeve has  
10 a bottom portion adapted to protrude beneath a bottom of the second outer electrode.

8. The device recited in Claim 1, wherein the at least one member comprises a plurality of members disposed about the support in spaced relation from each other and configured to surround a periphery of at least a portion of the target tissue.

9. The device recited in Claim 1, wherein the at least one member comprises a pair of members disposed in spaced-apart relation and adapted to provide at least one pair of opposite-polarity voltages approximately simultaneously on at least one electrode on each member.

10. The device recited in Claim 1, further comprising means for selectively activating a selected plurality of electrodes in a predetermined pattern.

11. The device recited in Claim 1, wherein the member has a portal therein for  
25 distributing a molecule therethrough, the portal adjacent at least one of the electrodes.

12. The device recited in Claim 1, wherein the member comprises an elongated nonconductive post and each electrode comprises a band wrapped at least partially circumferentially about the post, each electrode in spaced relation from an adjacent electrode.



13. The device recited in Claim 12, wherein the post comprises a plurality of posts affixed in spaced-apart relation to the support for surrounding at least a portion of a target tissue.

5 14. The device recited in Claim 13, further comprising means for activating a pair of electrodes on different posts for providing an electromagnetic pulse across at least a portion of the target tissue.

10 15. The device recited in Claim 14, wherein the activating means comprises means for activating successive pairs of electrodes in a preselected pattern.

16. A system for manipulating a molecule *in vivo* relative to a target tissue comprising:

15 a support and at least two elongated members affixed to and extending away from the support, a first member having at least one electrode and a second member having at least two discrete electrodes disposed in axial spaced-apart relation from each other and an insulating material interposed therebetween, each electrode being in independent circuit communication with a respective portion of a source of electrical energy;

20 the discrete electrodes being configured to establish a first electromagnetic field *in vivo* between selected electrodes sufficient to manipulate a molecule in three-dimensional space relative to a target tissue and a second electromagnetic field sufficient to cause transient permeability of a cell membrane within the target tissue.

25 17. The system recited in Claim 16, further comprising means for activating each electrode in a preselected pattern for optimizing entry of the molecule into the target tissue.

18. A method for achieving an improved distribution and delivery of a desired molecule from an initial body location into a target tissue comprising the steps of:

inserting at least one elongated member into a body generally adjacent a target tissue, each elongated member having at least two discrete electrodes, each electrode being in circuit communication with a respective portion of a source of electrical energy;

establishing a first electrical potential between a pair of electrodes sufficient to cause electromigration of the desired molecule from the initial location to a location in the target tissue; and

establishing a second electrical potential between a pair of electrodes higher than the first electrical potential sufficient to cause electroporation in the target tissue for enhancing a movement of the desired molecule into a cell thereof.

19. The method recited in Claim 18, wherein the elongated member inserting step comprises inserting a plurality of elongated members, and the establishing steps comprise establishing a first and a second electrical potential between a first electrode on a first elongated member and a second electrode on a second elongated member.

20. The method recited in Claim 19, wherein the establishing steps comprise establishing a series of first and second electrical potentials in a predetermined sequence of pulses.

21. The method recited in Claim 19, wherein the plurality of members are configured to generally surround a periphery of the target tissue.

22. The method recited in Claim 18, wherein the member has a lumen therein and a portal communicating therewith adapted to deliver the molecule from the lumen to the body location.

23. The method recited in Claim 18, further comprising the step, following the second establishing potential step, of establishing a third electrical potential between a pair of electrodes sufficient to cause electromigration of the desired molecule within the target tissue.

24. The method recited in Claim 23, wherein the establishing steps comprise establishing a series of first, second, and third electrical potentials in a predetermined sequence of pulses.

5 25. A method for delivering a bioactive molecule from an initial body location to a target tissue comprising the steps of:

inserting a member into a body generally adjacent or into a target tissue, each member bearing at least two discrete electrodes, each electrode being in circuit communication with a respective portion of a source of electrical energy;

10 activating a pair of electrodes to achieve an electromigration of the bioactive molecule from the initial location to a second location adjacent the target tissue; and

activating a pair of electrodes to achieve electroporation of a cell membrane within the target tissue sufficient to permit entry of the bioactive molecule from the second location into the cell interior.

15 26. A method for bringing two molecules into apposition at a desired target tissue site for permitting a reaction therebetween, a first molecule at a first area adjacent a target tissue site and a second molecule at a second area adjacent the target tissue site, the method comprising the steps of:

20 causing an electromigration of the first and the second molecule to a third area adjacent the target tissue site; and

permitting the first and the second molecule to react at the third area.

25 27. The method recited in Claim 26, wherein the electromigration causing step comprises the steps of:

inserting at least one elongated member into a body generally adjacent the target tissue, each elongated member having at least two discrete electrodes, each electrode in circuit communication with and differentially activatable by a source of electrical energy; and

establishing an electrical potential between a pair of electrodes sufficient to cause electromigration of the first and the second molecule in a desired direction toward the third area.

- 5           **28.**     A method for making a molecule electromanipulator comprising the steps of:  
                  affixing at least one elongated post to extend away from a support;  
                  affixing at least two discrete electrodes to the post in spaced-apart relation,  
each electrode differentially activatable;  
                  providing circuit communication between each electrode and a source of  
10   electrical energy, the electrodes configured to establish a low-level electromagnetic field *in vivo* between selected electrodes for manipulating a molecule relative to a target tissue and  
a higher-level electromagnetic field for causing transient permeability of a cell membrane within the target tissue; and  
                  providing switching means between each electrode and the electrical energy  
15   source to permit differential activation of each electrode.

**29.**     The method recited in Claim 28, further comprising means for controlling the switching means adapted to activate the electrodes in a preselected pattern.

1 / 6




FIG. 1.




FIG. 2A.




FIG. 2B.






FIG. 2C.

2 / 6






4 / 6




**FIG. 5.**





6/6

*FIG. 7.*

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/29911

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61N1/32

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	W0 96 39226 A (GENETRONICS INC) 12 December 1996 (1996-12-12) page 4, line 25 -page 9, line 9; figures ----	1,8-17
A	W0 99 37358 A (HOFFMAN GUENTER A ; GENETRONICS INC (US)) 29 July 1999 (1999-07-29) page 10, line 22 -page 14, line 14; figures ----	1,8-17
A	W0 94 22526 A (CENTRE NAT RECH SCIENT ;MIR LLUIS M (FR); ORLOWSKI STEPHANE (FR);) 13 October 1994 (1994-10-13) page 5, line 21 -page 9, line 8; figures ----	1,8-17
A	W0 96 00111 A (CYGNUS THERAPEUTIC SYSTEMS) 4 January 1996 (1996-01-04) page 4, line 12 -page 6, line 3; figures ----- -/--	1,16

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&amp;" document member of the same patent family

Date of the actual completion of the international search

18 August 2000

Date of mailing of the international search report

25/08/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Rakotondrajaona, C

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/29911

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 95 23211 A (SHOSHAN HERBERT Z ;UNIV RAMOT (IL)) 31 August 1995 (1995-08-31) page 4, line 16 -page 5, line 15; figures -----	1,16

# INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 99/29911

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9639226 A	12-12-1996	US 5702359 A	30-12-1997
		US 5993434 A	30-11-1999
		AT 185083 T	15-10-1999
		AU 702054 B	11-02-1999
		AU 5925996 A	24-12-1996
		CA 2218255 A	12-12-1996
		DE 69604509 D	04-11-1999
		DE 69604509 T	13-01-2000
		EP 0874663 A	04-11-1998
		ES 2140096 T	16-02-2000
		JP 11506630 T	15-06-1999
WO 9937358 A	29-07-1999	US 6009347 A	28-12-1999
		AU 2463399 A	09-08-1999
		EP 0977616 A	09-02-2000
WO 9422526 A	13-10-1994	FR 2703253 A	07-10-1994
		AU 6379494 A	24-10-1994
		DE 69412807 D	01-10-1998
		DE 69412807 T	18-03-1999
		EP 0693951 A	31-01-1996
		ES 2122256 T	16-12-1998
		US 5674267 A	07-10-1997
WO 9600111 A	04-01-1996	AU 2947795 A	19-01-1996
		CA 2194010 A	04-01-1996
		EP 0766579 A	09-04-1997
		JP 10511008 T	27-10-1998
WO 9523211 A	31-08-1995	AU 1930795 A	11-09-1995
		EP 0750663 A	02-01-1997
		US 5964726 A	12-10-1999